

Harvia HGP300XW - Technical Data

Features

User group Professionals

Power output 30 kW

Control type Wireless (WiFi)

Installation location Wall

Installation orientation Vertically

Colour Steel

Main material Steel

Water in connections G¾" male

Water out connections G½" female

Incoming water pressure bar min. 1,5 - max. 4,0

Steam output capacity (kg/h) 40.2

Control panel type Xenio WiFi

Use environment Interior - dry area

Remote use options MyHarvia WiFi

Prime energy/fuel Electric (high voltage 400V 3N~)

Weight

Net weight (kg) 25.6 kg



Measurements

Product height 490 mm

Product width 560 mm

Product depth 320 mm

Control panel width 85 mm

Control panel depth 24 mm

Control panel height 110 mm

Distances

Safety distance side 200 mm

(non-combustible materials)

Safety distance behind 0mm

(non-combustible materials)

Safety distance (ceiling) 100 mm

Safety distance (Floor 3ph) 140 mm

(depends on connections and

therefore from output, star/delta)

Safety distance (Floor 1ph) 140 mm

(depends on connections and

therefore from output, star/delta)

Installation opening height 705 mm

Installation opening width 805 mm

Control unit cable length 5 m

Sensor cable length 5 m



welldana

Mass. Pollet Pool Group

Power table 30

IP Class IPX2

Electrical Frequency 50/60 Hz

Fuses (400V3N~) pcs x ampers (3 x 25 A) x 2

Supply cable (400V 3N~) mm² 5 x 2.5 mm² / 5 x 2.5 mm²

Max. Connection power for light 100 W

Max. Connection power for fan 100 W

Max. Connection power for OUT1 / OUT2 50 W / 50 W

Electrical group options 400V 3N~

Logistics

EAN 6417659031011

Electrical number (STK) 8266795

Customs tariff number EU 85162999

Quantity 1

Packaging materials Cardboard, Plastic bag

Package height 575 mm

Package width 575 mm

Package depth 340 mm

Gross weight 27.3 kg